



bioKamino®

www.biokamino.com • info@biokamino.com



AUTOMATIC BURNER

BRUCIATORE AUTOMATICO

bioKamino®



TECNOLOGIA

- Serranda automatica
- Caricamento con pompa autoadescante interna
- Ciclo automatico di accensione e stabilizzazione della fiamma
- Accensione a basse temperature
- Accensione rapida*
- Controllo e regolazione fiamma automatici
- 3 livelli di fiamma
- Predisposizione per domotica
- Controllo con APP bioKamino
- Firmware bioKamino

*Ca. 3 minuti ad una temperatura ambiente di circa 15°C

TECHNOLOGY

- Automatic damper
- Filling with internal self-priming pump
- Automatic lighting cycle with flame stabilization
- Lighting at low temperatures
- Fast lighting*
- Automatic control and regulation of the flame
- 3 flame levels
- Suitable for home automation
- Control with APP bioKamino
- Firmware bioKamino

*Approx. 3 min at ambient temperature of 15°C degrees

SICUREZZA

- Sensore di movimento**
- Rilevatore perdite liquido**
- Sensore alta-temperatura**
- Blocco bambini
- Vasca di sicurezza
- Spegnimento rapido (ca. 90 sec.)

** Spegnimento automatico

CONSUMI ENERGETICI

- 60 W fase di accensione
- 10 W fase operativa
- Alimentazione elettrica: 12 V DC, 5 A, 60 W

SAFETY

- Motion detector**
- Leaks detector**
- High-temperature sensor**
- Child lock
- Safety tank
- Fast switch off (approx. 90 s)

** Automatic switch off

ENERGY CONSUMPTION

- 60 W lighting phase
- 10 W operative
- Power supply: 12 V DC, 5 A, 60 W

MODELLO (Model)	(A)	(B)	(C)	(D)	(E)	Peso (Weight)
BR700A	67cm	15cm	72 cm	25 cm	20 cm	16 Kg
BR1100A	107 cm	15 cm	112 cm	25 cm	20 cm	34 Kg
BR2000A	196 cm	18 cm	200 cm	25 cm	20 cm	57 Kg

I dati tecnici sono indicativi - Approximate technical datas

